Lecture 23: Data-Centric NLP

Instructor: Stephanie Schoch

CSCI 680: Natural Language Processing
Department of Computer Science, College of William & Mary
November 16, 2026


WILLIAM & MARY

Lecture Outline


- The what and why of data-centric NLP
- Training Data Attribution
- Better Data for In-Context Learning

Preliminaries: The What (and Why) of Data-Centric Approaches for LLMs


Large Language Models



Large Language Models



Large Language Models



Textual Entailment With ChatGPT

Idea: Determine if one sentence (hypothesis) can be inferred from another sentence (premise).

A nurse monitors a young child who appears to be post-op.
Question: A man watching over a person. True, False or Neither?

Textual Entailment With ChatGPT

Idea: Determine if one sentence (hypothesis) can be inferred from another sentence (premise).


A nurse monitors a young child who appears to be post-op.
Question: A man watching over a person. True, False or Neither?



Textual Entailment With ChatGPT

Idea: Determine if one sentence (hypothesis) can be inferred from another sentence (premise).

A nurse monitors a young child who appears to be post-op.
Question: A man watching over a person. True, False or Neither?



Answer: False

A nurse monitors a young child who appears to be post-op.
Question: A woman watching over a person. True, False or Neither?




Answer: True

Why the different responses?

stanfordnlp/**snli**

A nurse monitors a young child who appears to be post-op.	A woman watching over a person.	0 entailment

Prevalence of LLMs in Society & High Stakes Applications



https://x.com/EconomyApp/status/1622029832099082241/photo/1


LLMs and "Agentic AI" increasingly used in:

- **Healthcare**
- **Education**
- **Legal domain**
- **Scientific discovery**
- **…**


Today: Over 700 million weekly users!

How to Understand & Improve Model Performance?


LLMs model statistical patterns in text data.



Data-Centric: Center data as a critical component at each stage of model training & usage pipeline.




Benefits of Data-Centric Approaches



Banana

Data cleaning

- Mislabeled examples
- Outliers



Identify model weaknesses

- Performance on underlying task vs. shortcut features



Reduced training time

- Truncate dataset to only the informative examples
- Reduce redundant information

Better Data for Better Models

Training Data Attribution & Data Contribution

Identifying data attributions for model performance & behaviors



Fundamental question: Which data are beneficial or harmful to a model?

Goal: remove harmful data points & prioritize helpful data points

How: formalize a notion of benefit vs. harm, i.e. **value** or **contribution**

Identifying data attributions for model performance & behaviors



Fundamental question: Which data are beneficial or harmful to a model?

Goal: remove harmful data points & prioritize helpful data points

How: formalize a notion of benefit vs. harm, i.e. **value** or **contribution**



Manual inspection?

3 trillion tokens



Expensive (time & money)


Identifying data attributions for model performance & behaviors



Fundamental question: Which data are beneficial or harmful to a model?

Goal: remove harmful data points & prioritize helpful data points

How: formalize a notion of benefit vs. harm, i.e. **value** or **contribution**




Automated methods.

"If I trained the model without this data point, how would the performance of the model change?"

Data Contribution Estimation (DCE)


Value: how much each data point ***contributes*** to the overall model performance




Leave-One-Out (LOO)	$V(D) - V(D - \{i\})$

Marginal contribution of data point to entire training set.

Limitations of Leave-One-Out (LOO)




LOO = 0.85 - 0.85 = 0



LOO = 0.85 - 0.85 = 0


Filter low value data points



Fails to account for interactions between data points & data redundancy.

Data Contribution Estimation (DCE)


Value: how much each data point ***contributes*** to the overall model performance



Shapley Value	$\phi_i = C \sum_{S \subseteq D-\{i\}} \frac{V(S \cup \{i\}) - V(S)}{\binom{n-1}{\lvert S \rvert}}$

Weighted average marginal contribution of data point to every possible subset.

Shapley Values Address LOO Limitations



In Practice: Shapley-based DCE


Assume a well-designed value function

$$\phi_i(T, \mathcal{A}, v) = \sum_{S \subseteq T \setminus \{i\}} \frac{v(S \cup \{i\}) - v(S)}{\binom{n-1}{|S|}}$$

Exponentially expensive w.r.t. n **$O(2^n)$**

Evaluation: Helpful & Harmful Data


High-value data removal: High-value data should be critical for performance.





Dataset: Diabetes
Model: Logistic Regression

Noisy data detection: Complementary (low value data detection → application)




Scaling: Transferability of Value Estimates

Constraints to Address:


1. **Model constraint:** Shapley-based DCE requires repeatedly retraining the model → infeasible for LLMs
2. **Dataset constraint:** complexity grows exponentially with respect to number of data points.

Some properties affecting value estimates should be intrinsic to the data…



High-data removal → transferring values computed with logistic regression (LR) to an MLP model.

A Scalable By Design Method: TS-DShapley




Model constraint:
Compute value estimates using simple model trained using representation of data from targeted LLM.

Dataset constraint:
Utilize “sampling chains” and aggregate value estimates.

Application:
Estimate optimal low data removal index using SVM; **transfer** to LLM (i.e. use filtered data to fine-tune)

Filtering Fine-tuning Data Using TS-DShapley



Post-Hoc Training Data Attribution (TDA)


In-Run Attribution	Post-Hoc Attribution
• Computed while training the model. • Validation data must be known beforehand. • Checkpoints can still be saved.	• Computed after model training is completed. • Validation data can arrive after training. • Checkpoints are set.

$$\phi_z\left(U_{(1)}^{(t)}\right) = -\eta_t \nabla \ell(w_t, z^{(\mathrm{val})}) \cdot \nabla \ell(w_t, z), \quad t = 0, \ldots, T-1$$

Open-Weight Models	Fully Open-Source Models
GPT-2 Llama 3	Olmo 2 Pythia

"If a model has already been trained and released with checkpoints, how can we efficiently attribute downstream behavior to pretraining data without running attribution over every checkpoint?"

Checkpointed Attribution



Computational Bottleneck

Olmo 2
(> 600 … > 1000)


Pythia
(154)

Existing Heuristics

Checkpoint choice could change the attribution conclusions.

PRAM: Offline Checkpoint Selection for Post-Hoc TDA

Idea: Probe cheaply everywhere, then run full attribution only where attribution mass is high.




$$m_t(P_{\text{small}}, D_{\text{val}}^{\text{sel}}) = \sum_{q_j \in D_{\text{val}}^{\text{sel}}} \sum_{z_i \in P_{\text{small}}} |\alpha_t \, \tau_t(z_i; q_j)|$$


A. Sample small probe set.
B. Compute probe attribution across checkpoints.
C. Select high-mass checkpoints.
D. Run full attribution on selected subset.

PRAM: Results

PrAM recovers full-trajectory rankings with fewer checkpoints




Important checkpoints are trajectory dependent



Data Biases in ICL

Data Biases: Shortcut Behavior




Models can learn spurious correlations (i.e. statistical biases) between labels & features or presentation factors (e.g. label distribution)

Length is exploitable in fine-tuning → **analyze impact of length in ICL & potential for bias mitigation.**

In-Context Learning (and Unlearning) of Length Biases; **Stephanie Schoch**, Yangfeng Ji; *Published in NAACL 2025*

Do Models Learn Length Biases In-Context?



Method: Introduce distributional bias in ICL demonstrations.


Intuition: if length is exploitable feature, class performance on similar length test instances should be higher (and vice versa).

Do Models Learn Length Biases In-Context? Results


Model: Llama3 8B

Dataset: Hans


Condition: **True** sampled shortest instances; **False** sampled longest instances.



ICL: Random



ICL: Biased



Fine-Tuning


Holds when sampling from higher % of data (~4 tokens difference)

Also showed that you can also use ICL to counteract fine-tuned biases!


Data Curation

Fine-tuning on a few, high-quality examples → Compete with SOTA

LIMA: Less is more for alignment [Zhou et al., 2023]




1000 curated examples






Simply Scaling Fine-tuning Data is Not Enough

16-fold data increase (LLaMa 7B)



Scaling imitation data



[Gudibande et al., 2023]

Adversarial Robustness

Training Data Extraction From Pre-trained Language Models

[Ishihara, 2023]




Figure 2: The procedure of training data extraction attacks and possible defenses.

Training Data: Privacy & Memorization

- LLMs can (inadvertently) leak private data
  - Users find it acceptable to overshare with LLMs
- **Jailbreaking:** prompting a language model to make it reveal unsafe / private information

Privacy Ripple Effects from Adding or Removing Personal Information in Language Model Training [Borkar et al., 2025]





Figure 1: We explore a phenomenon we call *assisted memorization*, where unique PII that appeared earlier in the training at step $i-1$ and was not extracted at that step becomes extractable at a later step i, after fine-tuning on *other* PII.

Prompting & Jailbreaking

Jailbreaking: adversarial prompting (“jailbreaking”) can be used to generate potentially harmful outputs.



Aligned LLMs are not Adversarially Aligned

[Zou et al., 2023]

