Lecture 24: Interpretability

Instructor: Stephanie Schoch

CSCI 680: Natural Language Processing
Department of Computer Science, College of William & Mary
November 18, 2026

WILLIAM & MARY

Interpretability

The Urgency of Interpretability

April 2025

In the decade that I have been working on AI, I've watched it grow from a tiny academic field to arguably the most important economic and geopolitical issue in the world. In all that time, perhaps the most important lesson I've learned is this: the progress of the underlying technology is inexorable, driven by forces too powerful to stop, but the *way* in which it happens—the order in which things are built, the applications we choose, and the details of how it is rolled out to society—are eminently possible to change, and it's possible to have great positive impact by doing so. We can't *stop* the bus, but we can *steer* it. In the past I've written about the importance of deploying AI in a way that is positive for the world, and of ensuring that democracies build and wield the technology before autocracies do. **Over the last few months, I have become increasingly focused on an additional opportunity for steering the bus: the tantalizing possibility, opened up by some recent advances, that we could succeed at *interpretability*—that is, in understanding the inner workings of AI systems—*before* models reach an overwhelming level of power.**

[Source]

Dario Amodei & Demis Hassabis: Interpretability is **critical** for steering & safety

"We can't *stop* the bus, but we can *steer* it"
– Dario Amodei

If the time frame is as tight as you say, we don't have much time for care and thoughtfulness.

We *don't* have much time. We're increasingly putting resources into security and things like cyber and also research into, you know, controllability and understanding these systems, sometimes called mechanistic interpretability. And then at the same time, we need to also have societal debates about institutional building. How do we want governance to work? How are we going to get international agreement, at least on some basic principles around how these systems are used and deployed and also built?

[Source]

Lecture Outline


- Finishing Up: Data-Centric NLP, Adversarial Robustness
- Interpretability

Finishing Up: Data-Centric NLP, Adversarial Robustness


Fine-tuning on a few, high-quality examples → Compete with SOTA

LIMA: Less is more for alignment [Zhou et al., 2023]

Technique: Data Curation




1000 curated examples






Simply Scaling Fine-tuning Data is Not Enough

16-fold data increase (LLaMa 7B)



Scaling imitation data



[Gudibande et al., 2023]

Beyond Quality & Diversity, The Kinds of Data You Train On Matter: Privacy & Memorization

- LLMs can (inadvertently) leak private data
  - Users find it acceptable to overshare with LLMs
- **Jailbreaking:** prompting a language model to make it reveal unsafe / private information

Privacy Ripple Effects from Adding or Removing Personal Information in Language Model Training [Borkar et al., 2025]





Figure 1: We explore a phenomenon we call *assisted memorization*, where unique PII that appeared earlier in the training at step $i-1$ and was not extracted at that step becomes extractable at a later step i, after fine-tuning on *other* PII.


Prompting & Jailbreaking

Jailbreaking: adversarial prompting (“jailbreaking”) can be used to generate potentially harmful outputs.



Aligned LLMs are not Adversarially Aligned

[Zou et al., 2023]



Training Data Extraction From Pre-trained Language Models

[Ishihara, 2023]





Figure 2: The procedure of training data extraction attacks and possible defenses.

Interpretability

Capabilities vs. Transparency


Capability advancing faster than ability to **explain** it.


- Similar theme we talked about with evaluation



OpenAI's five stages of AI

Human Circuits vs. LLM Circuits







Thorpe & Fabre-Thorpe (2001), reproduced in Olshausen (2007)

Current estimates: ~86 billion neurons, 164 trillion synapses in cerebral neocortex alone

- And despite decades of neuroscience research, the brain's neural circuits and the mechanisms underlying complex cognition remain incompletely understood

Interpretability Research is Growing Quickly!







Source: (1) 2021–2026 flagship venues = ACL / EMNLP / ICLR / ICML / NeurIPS; (2) selected research blogs released from frontier AI laboratories (OpenAI, DeepMind, Anthropic).
Theme trends are title-keyword matches (mechanistic = SAE / circuit / superposition; CoT / reasoning; feature attribution / saliency) — a title-based lower bound.

[Source]

Approaches to Interpretability

Behavioral Interpretability

Let's see how the model behaves when we change the input



Mechanistic Interpretability

Let's open the box and look inside!

- Understand the internals of LLMs
  - How they function individually
  - How they are connected to enable LLM behaviors and capabilities

Behavioral Interpretability: Start with a Hypothesis

Example hypothesis: A classifier understands negation.

Original:
"The movie was great."
Expected: positive



Controlled Change:
"The movie was **not** great."
Expected: negative

Underlying idea:

1. Change one property
2. Predict what should happen
3. Compare against what the model does

CheckList: Test Linguistic Capabilities Systematically

[Rubio et al., 2020]

Three types of tests:

- **MFT:** Minimum Functionality Test
  - Simple examples to test behavior within capability
- **INV:** Invariance Test
  - Prediction should stay invariant
  - Label-preserving perturbations
- **DIR:** Directional Expectation Test
  - Expect a label to change in a certain way

Capability	Min Func Test	INVariance	DIRectional
Vocabulary	Fail. rate=15.0%	16.2%	C 34.6%
NER	0.0%	B 20.8%	N/A
Negation	A 76.4%	N/A	N/A
...			


Test case	Expected	Predicted	Pass?
A Testing **Negation** with ***MFT***	Labels: negative, positive, neutral		
`Template: I {NEGATION} {POS_VERB} the {THING}.`			
I can't say I recommend the food.	neg	pos	x
I didn't love the flight.	neg	neutral	x
...			
Failure rate = 76.4%			
B Testing **NER** with ***INV***	Same pred. (inv) after removals / additions		
@AmericanAir thank you we got on a different flight to [Chicago → Dallas].	inv	pos / neutral	x
@VirginAmerica I can't lose my luggage, moving to [Brazil → Turkey] soon, ugh.	inv	neutral / neg	x
...			
Failure rate = 20.8%			
C Testing **Vocabulary** with ***DIR***	Sentiment monotonic decreasing (↓)		
@AmericanAir service wasn't great. You are lame.	↓	neg / neutral	x
@JetBlue why won't YOU help them?! Ugh. I dread you.	↓	neg / neutral	x
...			
Failure rate = 34.6%			

Contrast Sets: Small Edits to Reveal Failures

[Gardner et al., 2020]

- **Motivation:** traditional benchmarks & datasets may have systemic gaps (e.g. annotator heuristics) that allow simple decision rules to work well on a test set
- **To create a contrast set:** Perturb test instances in small ways that are meaningful enough to (typically) change the gold label
- **Example:** NLVR2 visual reasoning dataset

Original Example:



Two similarly-colored and similarly-posed chow dogs are face to face in one image.


Example Textual Perturbations:

Two similarly-colored and similarly-posed **cats** are face to face in one image.

Three similarly-colored and similarly-posed chow dogs are face to face in one image.

Two **differently-colored but** similarly-posed chow dogs are face to face in one image.

Example Image Perturbation:



Two similarly-colored and similarly-posed chow dogs are face to face in one image.

Input Reduction to Expose Shortcuts

Pathologies of Neural Models Make Interpretations Difficult (Feng et al., 2018)


- **LOO (a type of feature attribution):** leave one word out, if word is important, model confidence should decrease
- Instead, they study how model's prediction is influenced by unimportant words
- Iteratively remove unimportant words
  - **Importance:** $g(x_i \mid \mathbf{x}) = f(y \mid \mathbf{x}) - f(y \mid \mathbf{x}_{-i})$
  - **So…** how to approximate how much the prediction would change if the word were removed?
    - dot product of word embedding and the gradient of the predicted probability with respect to the embedding $g(x_i \mid x) \approx e_i^\top \nabla_{e_i} f(y \mid x)$

SQuAD	
Context	In 1899, John Jacob Astor IV invested $100,000 for Tesla to further develop and produce a new lighting system. Instead, Tesla used the money to fund his Colorado Springs experiments.
Original	What did Tesla spend Astor's money on ?
Reduced	did
Confidence	0.78 → 0.91

Behavioral Analysis of Learned Bias

Models can learn spurious correlations (i.e. statistical biases) between labels & features or presentation factors (e.g. label distribution)

Example:



Method: Introduce distributional bias in ICL demonstrations.


Intuition: if length is exploitable feature, class performance on similar length test instances should be higher (and vice versa).

Behavioral Analysis of Learned Bias


Model: Llama3 8B

Dataset: Hans


Condition: **True** sampled shortest instances; **False** sampled longest instances.



ICL: Random



ICL: Biased



Fine-Tuning

Holds when sampling from higher % of data (~4 tokens difference)

You can also use ICL to counteract fine-tuned biases!

What Behavioral Interpretability Can and Cannot Tell Us

Answers some important *what* questions:


- Which changes matter
- Which biases are exploitable
- Where generalization fails

But doesn't answer some important *why* and *how* questions:

- Why model made a prediction
- What neurons encode certain information
- Whether a particular circuit is responsible

[DeYoung et al., 2020]

Rationales to help answer "how"?



- **Motivation:** Help make the question of ***how*** models make predictions
- **E**valuating **R**ationales **A**nd **S**imple **E**nglish **R**easoning (**ERASER**) benchmark
- Human annotation of "rationales" (supporting evidence)
- Separate **plausible** (would human consider evidence relevant) from **faithful** (did highlighted evidence actually influence prediction)

What about the attention mechanism?

- Previous viewpoint: attention provided some interpretability, in terms of what your model was using for prediction.
- “Attention is not explanation” (Jair & Wallace, 2019) optimized adversarial attention weights: same prediction, different “important features”



What about the attention mechanism?

Their claim: Just because a neural network assigns a high attention weight to a word does not mean that word is responsible for the model's prediction.

- Rather than describing the *why* for a prediction, they just describe how the model combines its internal representations

Follow-up from Wiegreffe & Pinter, 2019:

- *"In summary, due to the per-instance nature of the demonstration and the fact that model parameters have not been learned or manipulated directly, Jain and Wallace have not shown the existence of an adversarial model that produces the claimed adversarial distributions"*

Causal Gym: tests whether intervened information has a causal role in a behavior

[Arora et al., 2024]




Figure 1: The **CausalGym** pipeline: **(1)** take an input minimal pair $(\mathbf{b}, \mathbf{s})$ exhibiting a linguistic alternation that affects next-token predictions (y_b, y_s); **(2)** intervene on the base forward pass using a pre-defined intervention function that operates on aligned representations from both inputs; **(3)** check how this intervention affected the next-token prediction probabilities. In aggregate, such interventions assess the causal role of the intervened representation on the model's behaviour.

- Minimal pairs vary a targeted linguistic property.
- The next step is to intervene on an internal representation and test whether output preferences change.

TODOs:

- **Homework 3 Due: 11/20**

Next Class: Paper Discussion III